



Phone : ( 0265 ) 2637676 / 26366 55  
FAX : 0265 6580667  
Mobile : 09825182015/09427838761

# CKCO ENGINEERING WORKS

863/3, G.I.D.C. INDUSTRIAL ESTATE, MAKARPURA, VADODARA – 390 010.

<b>COVER FLUX - 5</b>	
<b>Introduction :</b>	
<b>COVER FLUX-5</b> is extremely effective exothermic powder which gives metal free dross. Proper use of <b>COVER FLUX-5</b> reduces metal loss in aluminium and it's alloys. It is mainly used as dross refining agent.	
<b>QUANTITY TO BE USE :</b>	
500 grams to 1000 grams ( 1 Kg ) per 100 kg. of melt.	
<b>DESCRIPTION :</b>	
<b>COVER FLUX-5</b> is available in a White powder form.	
<b>METHOD OF USE :</b>	
<ul style="list-style-type: none"><li>• When the melt is ready sprinkle <b>Cover Flux - 5</b> on the surface of the melt and rabble it.</li><li>• When dross accumulates on the surface of the melt add requisite amount of <b>Cover Flux-5</b> on the dross. This will separate metal from the dross and will give dross free metal.</li><li>• Then remove dross from the surface.</li><li>• It can also be used extensively to melt 100 % scrap in furnace or crucibles.</li></ul>	
<b>Precautions :</b>	
<b>CKCO FLUXES</b> should not be allowed to be exposed to the atmosphere when not in use.	
<b>Packing :</b>	
50 Kg. HDPE BAG.	